Safety data sheetaccording to Regulation (EC) No. 1907/2006Trade name:Red China Clay acc. MIL-STD-810Revision date:16 September 2020Version: 1493-0Print date:16 September 2020Page: 1 / 8



SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier Substance name/Trade name:

Red China Clay acc. MIL-STD-810

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses: Test dust Uses advised against: -

 1.3
 Details of the supplier of the safety data sheet

 Manufacturer/ Supplier:
 KSL staubtechnik gmbh

 Address/ PO Box:
 Westendstrasse 11

 Nat.-Ident./ Postcode/ city:
 DE - 89415 Lauingen

 Telephone/ Fax/ E-mail:
 +49 (0) 9072 / 95 00-0 / Fax

KSL staubtechnik gmbh Westendstrasse 11 DE - 89415 Lauingen +49 (0) 9072 / 95 00-0 / Fax no: -50 / info@ksl-staubtechnik.de

1.4 Emergency telephone number

+49 (0) 9072/ 95 00-0 (Accessibility: Mon-Thu 8am to 4pm, Fri 8am to 12pm)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

This product is contaminated with respirable quartz and is therefore classified as STOT RE2 according to the criteria defined in Regulation (EC) No. 1272/2008.

Depending on the handling and processing of the product, airborne respirable crystalline silica may form. Prolonged and/ or intensive inhalation of respirable crystalline silica may cause pulmonary disease (silicosis). The main symptoms of silicosis include cough and respiratory problems/ shortness of breath. Following exposure to respirable crystalline silica, suitable protection and monitoring measures should be taken. According to TRGS 906, activities involving respirable crystalline silica in the form of quartz and cristobalite have a carcinogenic effect on humans.

The product should be handled with great caution in order to avoid dust formation.

2.1.1 Classification according to Regulation (EC) No. 1272/2008 Hazard class: STOT RE2

Hazard class:STOT RE2Hazard category:2Hazard warnings:H373 Can cause damage to lungs through prolonged or repeated exposure if inhaled.This product contains between 1 and 10% respirable quartz.

2.2 Label elements

2.2.1 Label elements according to Regulation (EC) No. 1272/2008



 Signal word:
 Attention

 Hazard warning:
 H373: Can cause damage to lungs through prolonged or repeated exposure if inhaled.

 Safety precautions:
 P260: Do not breathe dust

 P284: In case of inadequate ventilation wear respiratory protection.
 P501: Dispose of contents (residual amounts)/ containers properly according to local regulations (avoid dust formation).

2.3 Other hazards

The product does not meet the criteria for PBT and vPvB substances according to Annex XIII of the REACH Regulation 1907/2006/EC.

SECTION 3: Composition/information on ingredients

3.1 Substances

This product is a mixture.

3.2 Mixtures

Composition/ information on ingredients Description of the mixture: Hazardous ingredients:

Red China Clay Quartz (SiO₂) This product contains between 1 and 10% respirable quartz, which is classified as STOT RE2.

Safety data sheetaccording to Regulation (EC) No. 1907/2006Trade name:Red China Clay acc. MIL-STD-810Revision date:16 September 2020Version: 1493-0Print date:16 September 2020Page: 2 / 8



Product identifier	CAS No.	EC No.	Concentration range [M%]	Classification according to Regulation (EC) No. 1272/2008
Silicon dioxide SiO2	14808-60-7	238-878-4	74 %	- H373 - STOT RE2 - Category 2
Aluminium oxide Al ₂ O ₃	1344-28-1	215-691-6	16 %	-
Calcium magnesium car- bonate CaMg(CO ₃) ₂	16389-88-1	240-440-2	7 %	-
Iron(III) oxide (Fe ₂ O ₃)	1309-37-1	215-168-2	3 %	-

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes:

If symptoms persist, it is advised to consult a doctor. Please specify substance/product and measures taken to the doctor. After inhalation:

Ensure supply of fresh air. Any dust in the throat and nasal passages should be cleared promptly. Consult a doctor in case of symptoms such as discomfort, cough or persistent irritation. In general, inhalation is to be avoided.

After skin contact: Wash with water and soap.

After eye contact:

If necessary, remove contact lenses and, holding the eyelid open, rinse the eye under running water to remove all particles. If possible, use an isotonic eye rinsing solution (0.9 % NaCl). Do not rub eyes when dry, since additional cornea damage could occur due to mechanical stress.

After ingestion:

Rinse mouth with plenty of water.

4.2 Most important symptoms and effects, both acute and delayed

Repeated inhaling of large amounts over a long period of time increases the risk of developing lung diseases (silicosis). The main symptoms of silicosis are cough and respiratory problems/ shortness of breath. Dust may cause irritation of the eyes and respiratory tract (caused by foreign bodies).

4.3 Indication of any immediate medical attention and special treatment needed

There are no known special measures.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable:

Suitable extinguishing media in the work area/ environment. **Unsuitable:** None

5.2 Special hazards arising from the substance or mixture None. Not combustible.

5.3 Advice for firefighters

None

5.4 Additional advice

No action is required because the mixture is not combustible.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Avoid dust formation. Wear protective clothing as described under Section 8. Follow the instructions for safe use, as described under Section 7.

6.1.2. For emergency responders

Emergency plans are not necessary. With high dust levels, respiratory protection is however required.



6.2 **Environmental precautions**

No special environmental precautions required.

Methods and material for containment and cleaning up 6.3

6.3.1 Notes for containment

Avoid dust generation. 6.3.2 Notes for clean-up

Avoid inhalation. Avoid dry sweeping. Use tested spraying and vacuum cleaning systems. Use protective equipment. 6.3.3 Advice on inappropriate containment and cleaning methods Blowing-off for cleaning purposes is not permitted.

6.4 Reference to other sections

See also Sections 8 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations on safe handling 7.1.1

Avoid dust formation and deposits. Handle packaged products carefully in order to prevent the packaging from bursting open. Areas subject to dust generation must be equipped with suitable ventilation systems. In case of inadequate dust removal in the workplace, wear suitable respiratory protection (in compliance with the EN 143 standard). Gloves compliant to the EN 374 standard are recommended.

Measures to prevent fire and explosion

No special measures required.

Measures to prevent aerosol and dust generation

Sweep only with an appropriate cleaning agent. For cleaning, use suitable methods as dry as possible - such as vacuum intake that do not cause dust generation.

Measures to protect the environment

No special measures required. 7.1.2 Advice on general occupational hygiene

During work do not drink, eat or smoke. Wash hands after use/ contact. In dusty atmosphere, use breathing masks and safety goggles.

7.2 Conditions for safe storage, including any incompatibilities

Advice on storage conditions Store in dry and sealed containers, possibly the original ones. Keep away from foodstuffs, drinks and tobacco. Requirements for storage rooms and vessels No special measures required. Storage class VCI: 10-13 (non-flammable solids)

7.3 Specific end use(s)

Industry and sector specific guidance

Convenient and economical application with suitable equipment depending on the intended purpose. For specific end uses (see Section 1.2), no additional information is available.

Further information can be found i. a. in the Agreement on Workers' Health Protection through the Good Handling and Use of Crystalline Silica and Products Containing it (see Section 16).

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters** National limit values 8.1.1

Components with workplace-related limit values to be monitored:

DNEL/ Chemical National Exposure Comment/ CAS No. EC No. PNEC identity limit value Legal provision type value Workplace-related limit General 1,25 (A) mg/m³ inhalative value dust limit value (respirable) **TRGS 900** Workplace-related limit 10 (E) mg/m³ General inhalative value dust limit value (inhalable) TRGS 900 List of carcinogenic not Silicon dioxide SiO₂ 14808-60-7 238-878-4 inhalative activities or processes available **TRGS 906**

* In Germany, there is currently available a limit value of 50 μg/m³.

Safety precautions, in particular the third and fourth section of the Hazardous Substances Ordinance (GefStoffV), must be observed.

The Occupational Exposure Limits (OEL) for respirable crystalline silica for EU countries, Norway and Switzerland can be found on www.nepsi.eu. For further information on the limit values of other countries, please consult a competent occupational hygiene expert or the local regulatory authority of the country involved.



8.1.2 International limit values

Components with international limit values that require monitoring at the workplace:

Chemical identity	CAS No.	EC No.	International limit value	Exposure type	Comment/ Legal provision
Aluminium oxide	1344-28-1	215-691-6	See GESTIS Da- tabase, interna- tional limit value*	inhalative	Respective international work threshold value

*The GESTIS-Database can be found under the following link: <u>http://limitvalue.ifa.dguv.de/</u>

8.2 Exposure controls

To comply with workplace-related limit values, combined technical and individual protection measures are often necessary. For the identified uses (Section 1.2), technical control devices and personal protection measures are recommended. Technical measures and the selection of appropriate processes have priority over the use of personal protective equipment.

8.2.1 Appropriate engineering controls

Avoid or minimise dust formation. Closed processes and local extraction devices are to be used in order to keep airborne dust concentrations below the permissible exposure limit value. With high dust content in the air, use a ventilation system. If dust formation cannot be avoided, the air must remain below exposure limit values through ventilation of the dust content. Organisational measures are to be applied, for example keeping people away from dusty areas.

Recommended measuring procedures for workplace-related measurements: see the professional association series of papers. 8.2.2 Individual protection measures, such as personal protective equipment

General

When the product is used as intended, no personal protective equipment is necessary. Treat the product in compliance with the safety instructions.

Eye/face protection

In case of dust generation, wear closed protective goggles according to EN 166.

Skin/hand protection

People suffering from dermatitis or with very sensitive skin should take appropriate precautions (e.g. wear gloves or use protective cream). Wash hands after working. The use of gloves compliant to the EN 374 standard is recommended.

Respiratory protection

Install effective exhaust ventilation and/ or sufficient ventilation. In case the permissible exposure limit values in the workplace are exceeded, a breathing mask must be worn in accordance with the regulations applied in the EU or current national regulations (e.g. particle filter P2 or P3 according to the EN 143 standard).

Occupational hygiene

During work do not drink, eat or smoke. Wash your hands before any breaks and after finishing work, and if necessary have a shower. Avoid contact with eyes and skin. After work, workers should wash or have a shower and use skin care products. Clean contaminated clothing, shoes, watches, etc., before re-using.

8.2.3 Environmental exposure controls

See also Sections 6 and 7.

Air

Prevent wind-blown dispersal. Compliance with dust emission limit values according to the Technical Instructions on Air Quality Control.

Water

Wastewater and groundwater regulations must be observed.

Ground

Compliance with the Federal Soil Protection Ordinance. No special control measures required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

THIO	information on basic physical and chemical properties				
(a)	Appearance: - Aggregate state	Powder - solid			
	- Colour	reddish			
(b)	Odour	odourless			
(c)	Odour threshold:	not applicable			
(d)	pH-value:	~5-9 (100 g/l at 20 °C)			
(e)	Melting point/ freezing point:	not applicable			
(f)	Initial boiling and boiling range:	not applicable			
(g)	Flash point:	not applicable			
(h)	Evaporation rate:	not applicable			
(i)	Flammability (solid, gas):	not applicable			
(j)	Lower explosive limits:	not applicable			
(k)	Vapour pressure:	not applicable			
(I)	Vapour density:	not applicable			
(m)	Relative density:	not specified			
(n)	Solubility:	negligible			
(0)	Partition coefficient:	not applicable			
(p)	Auto-ignition temperature:	not applicable			
(q)	Decomposition temperature:	not specified			
(r)	Viscosity:	not applicable as it is not a liquid			
(s)	Explosive properties:	None			
(t)	Oxidising properties:	not applicable, the mixture has no oxidising properties			

9.2 Other information

Not applicable



SECTION 10: Stability and reactivity

10.1 Reactivity

Inert product. Non-reactive.

10.2 Chemical stability

The mixture is stable.

10.3 Possibility of hazardous reactions

10.4 Conditions to avoid

Moisture and water during storage may cause lump formation and loss of product quality.

10.5 Incompatible materials

Calcium magnesium carbonate reacts with acids with formation of calcium and magnesium salts and CO₂.

10.6 Hazardous decomposition products

None when the product is used as intended.

Over 750°C or upon reaction with acids, calcium magnesium carbonate decomposes with formation of CO_2 (gas).

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Based on the available data, the classification criteria are not met. Skin corrosion/irritation

Based on the available data, the classification criteria are not met.

Serious eye damage/irritation

Based on the available data, the classification criteria are not met. Respiratory or skin sensitisation

Based on the available data, the classification criteria are not met.

Mutagenicity

Based on the available data, the classification criteria are not met. Carcinogenicity

Based on the available data, the classification criteria are not met. **Reproductive toxicity**

Based on the available data, the classification criteria are not met. Aspiration hazard

Based on the available data, the classification criteria are not met. Specific target organ toxicity — single exposure

Based on the available data, the classification criteria are not met. Specific target organ toxicity — repeated exposure

Repeated exposure to dust may cause pulmonary disease (silicosis).

Delayed and immediate effects, as well as chronic effects from short and long term exposure Immediate effects

Irritation of the eyes or respiratory tract caused by exposure to foreign bodies may occur.

Chronic effects with prolonged exposure

This product is contaminated with between 1 and 10% respirable quartz and is therefore classified as STOT RE2 according to the criteria defined in Regulation (EC) No. 1272/2008.

Prolonged and/ or intensive exposure to dust containing respirable crystalline silica may cause silicosis. This disease consists of a nodular pulmonary fibrosis caused by the inhalation and deposit of mineral dust.

In 1997, the International Agency for Research on Cancer (IARC) concluded that occupational exposure to crystalline silica can cause lung cancer in humans. However, the IARC specified that this no longer applies to all forms of exposure and all types of crystalline silica. (IARC-Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, volume 68, IARC, Lyon, France.)

In 2003, the EU's Scientific Committee on Occupational Exposure Limits (SCOEL) came to the conclusion that the main effect of inhalation of respirable crystalline silica dust in humans is silicosis. "We have sufficient information to conclude that there is an increased relative risk of lung cancer for people who are suffering from silicosis. Employees working in quarries and in the ceramic industry who are exposed to crystalline silica dust, but that are not suffering from silicosis, are apparently not affected by this increased risk of lung cancer. Therefore, it can be assumed that prevention of silicosis also reduces the risk of cancer..."(SCOEL SUM Doc 1994-final, June 2003).

There are numerous indications that an increased risk of lung cancer is restricted to people who are already suffering from silicosis. The protection of workers against silicosis should be ensured in compliance with the specified regulatory occupational exposure limit values and, if required, by ensuring implementation of additional risk management measures (see Section 16).



SECTION 12: Ecological information

For the product, no ecotoxicological data is available.

- 12.1 Toxicity Not relevant
- 12.2 Persistence and degradability Not relevant
- 12.3 Bioaccumulative potential Not relevant

12.4 Mobility in soil

Negligible

12.5 Results of PBT and vPvB assessment Not relevant

12.6 Other adverse effects

No known specific harmful effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Collect the product dry. Avoid formation of dust.

It can be disposed of together with household waste in compliance with local regulations. If necessary, coordinate disposal with the local competent authority.

Recommendation

Agree on the correct waste code with the disposal company.

Waste code according to the waste directory regulation (AVV)

010410 - dusty and powdery waste

Waste code according to the European List of Waste (LoW) For disposal within the EU, the currently valid waste code according to the European Waste Catalogue (EAV) must be used. Among other things, it is the task of the waste producer to assign his waste to industry- and process-specific waste codes according to the European Waste Catalogue (EAV).

Treatment of purified/unclean packaging

150106 - mixed packaging suitable for material recycling

The formation of dust as a result of the remains of packaging should be avoided. Store contaminated packaging materials in closed containers. The recycling and disposal of packaging materials must take place in accordance with local applicable regulations and should be performed by a certified waste management company. Do not use packaging materials several times.

SECTION 14: Transport information

With respect to transport regulations, the product is not hazardous (ADR, RID, ADN, IMDG, ICAO/IATA).

14.1 UN number

Not applicable

- **14.2 UN proper shipping name** Not applicable
- 14.3 Transport hazard class(es) Not applicable
- 14.4 Packing group Not applicable
- 14.5 Environmental hazards Not applicable
- 14.6 Special precautions for user

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code Not applicable



SECTION 15: Regulatory information

15.1 Safety, health and environment regulations/legislation for the substance or mixture

The product does not fall within the registration requirement of EC Regulation 1907/2006 (REACH).

EU regulations

Among others, the EC Regulation 1907/2006 (REACH)

National regulations

When handling this product, the following valid legal provisions are i. a. to be complied with

AwSV Water hazard class: nwg - not hazardous for water

TRGS 500 "precautions" TRGS 559 "Mineral dust"

TRGS 900 "Work-place related limit values"

TRGS 906 "List of carcinogenic activities or processes according to §3 paragraph 2 no. 3 GefStoffV"

Technical Instructions on Air Quality Control Regulation on occupational health care (ArbMedVV)

Basic principles of the Institution for Statutory Accident Insurance and Prevention on occupational medical examinations

15.2 Chemical safety assessment

A safety assessment has not been carried out.

SECTION 16: Other information

16.1 Changes to the previous version First version.

16.2 Abbreviations and acronyms

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ArbMedVV	Verordnung zur arbeitsmedizinischen Vorsorge (Regulation on occupational health care)
BImSchV	Bundes-Immissionsschutzverordnung (German Federal Emission Control Act)
BG	Berufsgenossenschaft (Institution for Statutory Accident Insurance and Prevention)
CAS	Chemical Abstracts Service
CLP	Classification, labelling and packaging (Regulation (EC) No. 1272/2008)
GefStoffV	Gefahrstoffverordnung (Hazardous Substances Ordinance)
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
ICAO	International Civil Aviation Organisation
IMDG	International agreement on the Maritime transport of Hazardous Goods
PBT	Persistent, bio-accumulative and toxic
REACH	Registration, Evaluation and Authorisation of Chemicals (Regulation (EC) 1907/2006)
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SCOEL	Scientific Committee for Occupational Exposure Limits
SDS	Safety Data Sheet
STOT	Specific Target Organ Toxicity
SWeRF	Size Weighted Relevant Fine Fraction
TRGS	Technische Regeln für Gefahrstoffe (Technical rules for hazardous substances)
VCI	Verband der chemischen Industrie e.V. (Registered association of the chemical industry)
vPvB	Very persistent, very bioaccumulative
AwSV	Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Regulation on plants for handling sub-
	stances hazardous to water)

16.3 Literature references and sources of data

With regard to the sources of key data and technical information, we refer, among others, to the information provided by the raw material supplier/ manufacturer or the ECHA Classification and Labelling Inventory.

16.4 Methods compliant with article 9 of Regulation (EC) No. 1272/2008 used to evaluate information for the purpose of classification

No own assessment of the mixture has been made.

Bridging principles for the classification of mixtures according to Regulation (EC) No. 1272/2008, article 6, paragraph 5 have been applied.

The classification of the water pollution class of this mixture has been carried out according to AwSV. The respirable dust content of the quartz component (SiO₂) was determined using the SWeRF method.

16.5 Training appropriate for workers

In addition to training programmes for employees on the topics of health, safety and environment, companies must ensure that their employees read and understand this safety data and are able to implement its requirements. Employees must be informed of the presence of crystalline quartz and trained on the intended use of the product.

Safety data sheet according to Regulation (EC) No. 1907/2006				
Trade name:	Red China Clay acc. MIL-STD-810			
Revision date:	16 September 2020	Version: 1493-0		
Print date:	16 September 2020	Page: 8/8	KSL staubtechnik	

16.6 Social dialogue on respirable crystalline silica

On 25 April 2006, the cross-sector "Agreement on Workers' Health Protection through the Good Handling and Use of Crystalline Silica and Products Containing it" was signed. This autonomous agreement, funded by the European Commission, is based on guidelines concerning good practices. The conditions specified in the agreement came into force on 25 October 2006. The agreement was published in the Official Journal of the European Union (2006/C 279/02). The text of the agreement, its annexes and the guidelines concerning good practices can be found at http://www.nepsi.eu. These provide useful information and guidelines concerning good practices can be found at http://www.nepsi.eu. These provide useful information and guidelines concerning good practices can be found at http://www.nepsi.eu. These provide useful information and guidelines concerning good practices can be found at http://www.nepsi.eu. These provide useful information and guidance for the handling of products containing respirable crystalline silica. References are available at EUROSIL (European Association of Industrial Silica Producers).

Occupational exposure limits can also be found at <u>www.nepsi.eu</u>.

16.7 Disclaimer

The information contained in this safety data sheet describes the safety requirements of our product and is based on our current level of knowledge. It implies no guarantee of the product properties and does not justify a contractual legal relationship. This safety data sheet serves the user as reference information. Although this safety data sheet has been drawn up with great care, no guarantee for data accuracy, and no liability for the consequences of printing, typeset or transcription errors can be accepted. The existing laws, regulations and rule systems, including those not mentioned in this data sheet, must be complied with by the recipient of our products under their own responsibility.