esplas H60 Axx, H130 Axx

Revision date: 22 November 2017 Version: 734-4 Print date: 22 November 2017 Page: 1/7



SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 **Product identifier**

esplas H60 A10, A30, A50 / esplas H130 A10, A30, A50 Substance name/ Trade name:

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Separating and test dust

Uses advised against:

Details of the supplier of the safety data sheet

Manufacturer/ Supplier: KSL staubtechnik gmbh Address/ PO Box: Westendstrasse 11 Nat.-Ident./ Postcode/ city: Telephone/ Fax/ E-mail: DE - 89415 Lauingen

+49 (0) 9072 / $9\bar{5}$ 00-0 / Fax no: -50 / info@ksl-staubtechnik.de

Emergency telephone number

+49 (0) 9072/ 95 00-0 (Accessibility: Mon-Thu 8am to 4pm, Fri 8am to 12pm)

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 2.1.1

Hazard class: Eye Irrit. 2 – Serious eye damage/irritation

Hazard category:

H319 Causes serious eye irritation Hazard warnings:

2.2 **Label elements**

2.2.1 Label elements according to Regulation (EC) No. 1272/2008



GHS07

Signal word: Attention

Causes serious eye irritation Hazards: H319 P264 Wash skin thoroughly after use Safety precautions:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 If eye irritation persists: Get immediate medical advice/attention.

2.3 Other hazards

Slight skin irritation.

Harmful to aquatic organisms.

Flammable solid.

Dust and air can form mixtures that may explode - risk of dust explosion. Under normal use, adverse health effects are not known or expected.

SECTION 3: Composition/information on ingredients

3.1 Substances

The product is a mixture.

3.2

Composition/ information on ingredients

Description of the mixture: esplas H60 Axx, H130 Axx

Hazardous ingredients: Adipic acid

Trade name: esplas H60 Axx, H130 Axx

Revision date: 22 November 2017 Version: 734-4 Print date: 22 November 2017 Page: 2 / 7



Product identifier	CAS No.	EC No.	Concentra- tion range [M%]	Reg. no. (REACH)	Classification according to Regulation (EC) No. 1272/2008
Polymethyl methacrylate	9011-87-4	-	49.9-89.8%	exempt	Not applicable
Adipic acid	124-04-9	204-673-3	10-50%	exempt	- Eye Irrit. 2 - Category 2 - H319

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes:

If symptoms persist, it is advised to consult a doctor. Please specify substance/product and measures taken to the doctor.

After inhalation:

Move to fresh air. Consult a doctor.

After skin contact:

Wash with plenty of soap and water. Remove/Take off immediately all contaminated clothing and shoes. Consult a doctor.

After eye contact:

While protecting the uninjured eye, rinse the eye under running water for 15 minutes with eyelids held open wide. Remove contact lenses, if present and easy to do. Continue rinsing. Consult a doctor.

After ingestion:

Rinse mouth with plenty of water. Spit out the fluid once more. Do not induce vomiting. Consult a doctor.

4.2 Most important symptoms and effects, both acute and delayed

Dust may cause irritation of the eyes and respiratory tract.

4.3 Indication of any immediate medical attention and special treatment needed

Treat according to symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable:

Water mist spray, alcohol-resistant foam, dry powder, carbon dioxide

Unsuitable:

Solid water jet: Hazard of dust cloud mixture

5.2 Special hazards arising from the substance or mixture

Dust and air may form explosive mixtures.

With prolonged heating above 250°C (referring to polymethyl methacrylate), hazardous decomposition products (e.g. methyl methacrylate, oxidised hydrocarbons, carbon monoxide, carbon particles and carbon dioxide) can form. Inhalation of vapours in high concentrations may irritate the respiratory tract.

5.3 Advice for firefighters

Wear a self-contained breathing apparatus and suitable protective clothing.

5.4 Additional advice

Take precautionary measures against static charges. Avoid dust formation.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Wear protective clothing as described under Section 8. Do not inhale vapours/mist/gas. Ensure adequate ventilation. Guide people to safety. Avoid inhalation of dust. Follow the instructions for safe use, as described under Section 7. Avoid dust formation. Remove all sources of ignition.

6.1.2. For emergency responders

Emergency plans are not necessary. With high dust levels, respiratory protection is however required.

6.2 Environmental precautions

No direct discharge of aqueous suspensions in water. Keep the substance away from waters, sewerage or soil.

6.3 Methods and material for containment and cleaning up

6.3.1 Notes for containment

Avoid dust generation.

esplas H60 Axx, H130 Axx

Revision date: 22 November 2017 Version: 734-4 Print date: 22 November 2017 Page: 3 / 7



6.3.2 Notes for clean-up

Absorb or suck the mixture mechanically. For disposal, collect it in the containers provided for this purpose, according to local regulations. Use approved industrial vacuum cleaners or suction systems for potentially explosive areas.

Advice on inappropriate containment and cleaning methods

Blowing-off for cleaning purposes is not permitted.

6.4 Reference to other sections

As to disposal, please refer to Section 13 of the Safety Data Sheet (SDS).

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations on safe handling

Avoid formation of dust as well as dust deposits. If dust should form, ensure suitable ventilation. Information on safety precautions can be found in Section 2.2.

Measures to prevent fire and explosion

Take precautionary measures against static charges. Avoid dust formation. Keep away from sources of ignition. In case of fire, cool endangered product with water.

Measures to prevent aerosol and dust generation

Sweep only with an appropriate cleaning agent. For cleaning, use suitable methods as dry as possible - such as vacuum intake that do not cause dust generation.

Measures to protect the environment

Keep the substance away from waters, sewerage or soil.

Advice on general occupational hygiene

During work do not drink, eat or smoke. Wash hands after use/ contact. In dusty atmosphere, use breathing masks and safety goggles.

Conditions for safe storage, including any incompatibilities

Advice on storage conditions

Store containers dry. Do not store together with explosives and/or oxidising substances.

Requirements for storage rooms and vessels

Store in dry and sealed containers, possibly the original ones.

Storage class

VCI: 11 (flammable solids)

Specific end use(s)

Industry and sector specific guidance

For specific end uses (see Section 1.2), no additional information is available.

Not intended for thermal processing.

SECTION 8: Exposure controls/personal protection

Control parameters

Components with workplace-related limit values to be monitored:

Chemical identity	CAS No.	EC No.	National limit value	Exposure type	Comment/ Legal provision
General dust limit value	-	-	1,25 (A) mg/m ³ (respirable)	inhalative	Workplace-related limit value TRGS 900
General dust limit value	-	-	10 (E) mg/m ³ (inhalable)	inhalative	Workplace-related limit value TRGS 900

The international limit values for adipic acid can be found in the GESTIS database at the following link:

http://limitvalue.ifa.dguv.de/WebForm_ueliste.aspx

For further information on the limit values of other countries, please consult a competent occupational hygiene expert or the local regulatory authority of the country involved.

8.2 **Exposure controls**

To comply with workplace-related limit values, combined technical and individual protection measures are often necessary. Recommended measuring procedures for workplace-related measurements: see the professional association series of papers. Technical measures and the selection of appropriate processes have priority over the use of personal protective equipment.

8.2.1 Appropriate engineering controls

For the identified uses (Section 1.2), technical control devices and personal protection measures are recommended. Ventilate as required to control dust in the air. With high dust content in the air, use an explosion-proof ventilation system.

Individual protection measures such as personal protective equipment

Treat the product in compliance with the safety instructions.

Eye/face protection

In case of dust generation, wear closed protective goggles according to the EN 166 Standard.

Trade name: esplas H60 Axx, H130 Axx

Revision date: 22 November 2017 Version: 734-4
Print date: 22 November 2017 Page: 4 / 7



Skin/hand protection

Wear protective gloves according to the EN 374 Standard.

Respiratory protection

In case the exposure limit values are exceeded (e.g. with open handling of powdery product), a suitable breathing mask with P2 particle filter must be worn according to Standard 143. In the unlikely event of formation of particularly high dust concentrations, a self-contained breathing apparatus may be advisable.

Occupational hygiene

During work do not drink, eat or smoke. Wash your hands before any breaks and after finishing work, and if necessary have a shower. Avoid contact with eyes and skin. After work, workers should wash or have a shower and use skin care products. Clean contaminated clothing, shoes, watches, etc., before re-using.

8.2.3 Environmental exposure controls

See Sections 6 and 7. No further action is required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

(a) Appearance: - Aggregate state Powder - solid

- Colour varying – white, whitish, greyish, reddish

(b) Odour weak

(c) Odour threshold: no data available
(d) pH-value: 2.5 - 3 (100 g/l at 20°C)

(e) Melting point/ freezing point: Adipic acid 151°C

Acrylic polymer based on methyl methacrylate 105°C - 130°C.

 (f)
 Initial boiling and boiling range:
 not applicable

 (g)
 Flash point:
 ~ 200°C

 (h)
 Evaporation rate:
 not applicable

 (i)
 Flammability (solid, gas):
 no data available

 (j)
 Lower explosive limits:
 ≥ 30 g/m³

 (k)
 Vapour pressure:
 0.1 hPa at 20°C

(I) Vapour density: no information available (m) Relative density: no information available (n) Solubility: partially soluble in water

readily soluble, e.g. in esters, ketones and chlorinated hydrocarbons

(o) Partition coefficient: no data available
(p) Auto-ignition temperature: > 350°C
(q) Decomposition temperature: > 330°C

(r) Viscosity: not applicable as it is not a liquid

(s) Explosive properties: explosive (dust explosion class ST1) in dust-air mixture

and not pyrotechnic.

(t) Oxidising properties: not applicable, the mixture has no oxidising properties

9.2 Other information

Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

In case of appropriate storage and handling, no hazardous reactions are known.

Dust explosion hazard with dust-air mixtures.

10.2 Chemical stability

Under normal ambient temperature and pressure the mixture is stable.

10.3 Possibility of hazardous reactions

No hazard under normal storage conditions. Exothermic reaction with strong acids.

10.4 Conditions to avoid

Temperatures > 105°C, moisture

10.5 Incompatible materials

Strong oxidising agents Reacts with bases

10.6 Hazardous decomposition products

None if used as intended.

With prolonged heating above 250°C (referring to polymethyl methacrylate), hazardous decomposition products (e.g. methyl methacrylate, oxidised hydrocarbons, carbon monoxide, carbon particles and carbon dioxide) can form.

Trade name: esplas H60 Axx, H130 Axx

Revision date: 22 November 2017 Version: 734-4 Print date: 22 November 2017 Page: 5 / 7



SECTION 11: Toxicological information

11.1 Information on toxicological effects

For the product, no toxicological information is available. The information refers to the admixed adipic acid.

Acute oral toxicity LD₅₀ 5.560 mg/kg - rat

Not classified as harmful if swallowed.

Acute inhalation toxicity $LC_{50} - 4h: > 7.7 \text{ mg/l} - \text{rat}$

Dust / at this dose, mortality was not observed. Not classified as harmful after inhalation.

Acute dermal toxicity LD₅₀: > 7.940 mg/kg - rat

At this dose, mortality was not observed. Not classified as harmful after contact with skin.

Skin corrosion/irritation Slight irritation

Serious eye damage/irritation Risk of serious damage to eyes

Respiratory or skin sensitisation guinea pigs

No skin sensitisation reaction was observed.

MutagenicityGenotoxicity in vitro: In vitro tests did not show any mutagenic effects
Genotoxicity in vivo: In vivo tests did not show any mutagenic effects

Carcinogenicity ra

Study results following oral administration give no indication of any

carcinogenic potential.

Reproduction toxicityToxicity for reproduction: no reproduction toxicity

Developmental toxicity: rat/mouse/rabbit

No teratogenic (harmful to development) effect has been observed.

Aspiration hazard No data available Specific target organ toxicity — single exposure

The substance or mixture is not classified as having target organ toxicity in the event of

single exposure.

Specific target organ toxicity — repeated exposure

Oral exposure 24 months - rat

NOAEL: 750 mg/kg

Assessment:

The substance or mixture is not classified as having target organ toxicity in the event of

repeated exposure.

SECTION 12: Ecological information

12.1 Toxicity

For the product, no ecotoxicological data is available. Due to the consistency of the product, no negative ecological effects are to be expected based on current knowledge.

The following information refers to the admixed adipic acid.

It is assumed that adipic acid has a low toxicity for aquatic organisms.

Toxicity for fish: LC50 – 96 h: > 1.000 mg/l Danio rerio (zebrafish)

Toxicity for daphnia: EC50 – 48 h: 46 mg/l Daphnia magna (great water flea)

NOEC – 21 days: 6.3 mg/l Daphnia magna (great water flea)

Toxicity for aquatic plants: EC50 – 72 h: 59 mg/l Pseudokirchneriella subcapitata

Toxicity for microorganisms: EC50 – 3 h: 4.747 mg/l - activated sludge

Ecotoxicological assessment

Acute aquatic toxicity: Harmful to aquatic organisms

12.2 Persistence and degradability

The product is easily biodegradable in soil (referring to adipic acid)

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

A PBT/vPvB assessment is not available, since a chemical safety assessment is not required / has not been carried out.

12.6 Other adverse effects

Unknown.

esplas H60 Axx, H130 Axx

Revision date: 22 November 2017 Version: 734-4 Print date: 22 November 2017 Page: 6 / 7



SECTION 13: Disposal considerations

13.1 Waste treatment methods

It can be disposed of together with household waste in compliance with local regulations. Collect the product dry. Do not dispose of into drains or surface waters.

Recommendation

Agree on the correct waste code with the disposal company.

Waste code according to the European List of Waste (LoW)

070199 - Wastes from the manufacture, preparation, distribution and use of organic basic chemicals

Treatment of purified/unclean packaging

150106 - mixed packaging suitable for material recycling

SECTION 14: Transport information

With respect to transport regulations, the product is not hazardous (ADR, RID, ADN, IMDG, ICAO/IATA).

14.1 UN number

Not applicable

14.2 UN proper shipping name

Not applicable

14.3 Transport hazard class(es)

Not applicable

14.4 Packing group

Not applicable

14.5 Environmental hazards

Not applicable

14.6 Special precautions for user

No special measures

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environment regulations/legislation for the substance or mixture

The product does not fall within the registration requirement of EC Regulation 1907/2006 (REACH).

EU regulations

National regulations

When handling this product, the following valid legal provisions are i. a. to be complied with

VwVwS: Water hazard class 1 - slightly hazardous for water

Hazardous Substances Ordinance (GefStoffV)

TRGS 500 "precautions"
TRGS 510 "storage of hazardous substances in portable containers"

TRGS 900 "Work-place related limit values"

Technical Instructions on Air Quality Control

Regulation on occupational health care (ArbMedVV)

Basic principles of the Institution for Statutory Accident Insurance and Prevention on occupational medical examinations

15.2 Chemical safety assessment

A safety assessment has not been carried out.

SECTION 16: Other information

16.1 Changes to the previous version

Removal of outdated guidelines under point 2 and point 3 Editorial revision

Trade name: esplas H60 Axx, H130 Axx

Revision date: 22 November 2017 Version: 734-4 Print date: 22 November 2017 Page: 7 / 7



16.2 Abbreviations and acronyms

ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road ArbMedVV Verordnung zur arbeitsmedizinischen Vorsorge (Regulation on occupational health care) Berufsgenossenschaft (Institution for Statutory Accident Insurance and Prevention)

CAS Chemical Abstracts Service

CLP Classification, labelling and packaging (Regulation (EC) No. 1272/2008)

ECHA European Chemicals Agency

GefStoffV Gefahrstoffverordnung (Hazardous Substances Ordinance)

IATA International Air Transport Association ICAO International Civil Aviation Organisation

IMDG International agreement on the Maritime transport of Hazardous Goods

PBT Persistent, bio-accumulative and toxic

REACH Registration, Evaluation and Authorisation of Chemicals (Regulation (EC) 1907/2006)

RID Regulations concerning the International Carriage of Dangerous Goods by Rail

SDS Safety Data Sheet

TRGS Technische Regeln für Gefahrstoffe (Technical rules for dangerous substances)

VCI Verband der chemischen Industrie e.V. (Registered association of the chemical industry)

vPvB Very persistent, very bioaccumulative

VwVwS Verwaltungsvorschrift wassergefährdende Stoffe (Administrative Regulation on the Classification of Substances

hazardous to Waters into Water Hazard Classes)

16.3 Literature references and sources of data

With regard to the sources of key data and technical information we refer, among others, to the information provided by the raw material supplier/ manufacturer or the ECHA Classification and Labelling Inventory

16.4 Methods compliant with article 9 of Regulation (EC) No. 1272/2008 used to evaluate information for the purpose of classification

No own assessment of the mixture has been made.

Bridging principles for the classification of mixtures according to Regulation (EC) No. 1272/2008, article 6, paragraph 5 have been applied.

The classification of the water pollution class of this mixture has been carried out according to Point 3, Annex 4, of the VwVwS.

16.5 Training appropriate for workers

In addition to training programmes for employees on the topics of health, safety and environment, companies must ensure that their employees read and understand this safety data and are able to implement its requirements.

16.6 Disclaimer

The information contained in this safety data sheet describes the safety requirements of our product and is based on our current level of knowledge. It implies no guarantee of the product properties and does not justify a contractual legal relationship. This safety data sheet serves the user as reference information. Although this safety data sheet has been drawn up with great care, no guarantee for data accuracy, and no liability for the consequences of printing, typeset or transcription errors can be accepted. The existing laws, regulations and rule systems, including those not mentioned in this data sheet, must be complied with by the recipient of our products under their own responsibility.